

# WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
426	STD	11-43	57-15	234	252	191	206	.230	.230	.345	.345	.025	.023	.010	.022	107	114	
130	1	15-57	69-26	252	275	202	205	.230	.230	.335	.328	.035	.028	.010	.017	107	110	GT
127	2	31-65	66-35	276	281	214	215	.265	.262	.386	.379	.052	.047	.012	.014	106	108	GT500
212	3	35-72	73-34	287	287	230	230	.277	.277	.401	.401	.065	.060	.015	.015	108	110	
485	3	35-50	73-32	264	286	214	225	.262	.264	0.381	.382	.062	.058	.012	.014	103	110	
126	4	34-64	65-32	278	277	225	223	.240	.235	.342	.333	.064	.058	.018	.020	107	107	A2
125	4	50-87	82-48	316	309	246	242	.267	.260	.381	.368	.085	.075	.020	.022	108	108	A3
124	5	59-69	94-57	308	330	249	251	.273	.273	.390	.388	.095	.088	.020	.022	105	107	A6
556	5	39-71	74-36	290	290	244	245	.306	.306	.439	.437	.094	.082	.020	.022	106	108	
132	6	66-80	90-64	326	333	263	265	.285	.285	.413	.413	.115	.110	.015	.015	100	102	A8

**CODE: FORD 1600**  
 PERFORMANCE - 44G  
 STANDARD - 44S  
 BILLET - EP51  
 EXCHANGE - DEP FORD 1600

**NOTES:** SAME CAM FITS ALL ANGLIA, CORTINA, ESCORT  
 NARROW AND WIDE LOBE  
 SPRINGS SHOULD BE ALWAYS CHECKED ABOVE #130  
 2 TYPES OF CAM FOLLOWERS  
 EARLY STEM DIA 11MM (CF2)  
 LATER STEM DIA 13MM (CF3)

**1600**

**ROCKER RATIO 1.5**

**FORD**