

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
407	1	24-54	69-22	260	270	192	198	.250	.250	.433	.433	.030	.022	HYD	HYD	107	113	
521	2	27-67	72-29	274	282	202	207	.265	.265	.458	.458	.035	.032	HYD	HYD	110	110	
408	3	26-63	68-24	270	272	208	209	.280	.280	.484	.484	.040	.037	HYD	HYD	109	110	
409	4	30-70	70-30	280	280	217	217	.285	.285	.493	.493	.052	.048	HYD	HYD	108	111	
218	4-5	35-75	75-35	290	290	225	225	.278	.278	.481	.481	.067	.060	HYD	HYD	108	108	
410	5	38-78	78-38	295	295	226	226	.305	.305	.528	.528	.060	.055	HYD	HYD	109	111	
219	6	40-80	80-40	300	300	241	241	.300	.300	.519	.519	.075	.070	HYD	HYD	107	111	
668	1EFI	18-54	64-16	251	260	193	194	.256	.258	.443	.446	.020	.018	HYD	HYD	111	114	
551	2EFI	24-62	65-22	266	267	205	205	.270	.270	.467	.467	.038	.035	HYD	HYD	110	110	
404	2	20-57	62-18	256	260	205	206	.282	.284	.488	.491	.036	.034	HYD	HYD	109	111	TURBO

CODE: FORD 4.1 HYD
 PERFORMANCE - 46G
 STANDARD - 46S
 BILLET - EP 142
 EXCHANGE - DEP 4.1
 CAM FOLLOWERS -RHT900

ROCKER RATIO 1.73

4.1 HYD - XFLOW

FORD