

# WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
572	STD	18-74	70-16	270	266	202	200	.258	.258					HYD	HYD	115	116	
404	1	20-57	62-18	256	260	205	206	.282	.284			.036	.034	HYD	HYD	109	111	
699	2	20-65	70-20	265	270	205	207	.265	.267			.026	.026	HYD	HYD	113	114	
700	3	22-67	70-22	269	272	210	210	.278	.278			.029	.029	HYD	HYD	114	114	
634	3	26-58	77-26	264	283	206	215	.280	.285			.038	.035	HYD	HYD	106	116	
409	4	30-70	70-30	280	280	217	217	.285	.285			.052	.048	HYD	HYD	108	111	
741		26-62	64-24	268	268	230	230	.381	.381			.067	.062	.020	.020	109	109	
427	SS	29-67	65-27	276	272	199	199	.258	.258			.028	.025	HYD	HYD	109	110	
228T		22-67	69-20	268	268	208	209	.294	.294			.020	.024	HYD	HYD	113	115	
417		43-81	77-41	304	298	241	240	.333	.333			.086	.083	HYD	HYD	111	108	

**CODE: HOLDEN 304VN**  
 PERFORMANCE - 48G  
 STANDARD - 48S  
 BILLETT - EP248  
 EXCHANGE - NIL

**NOTES: EFI MOTOR**

304VN

HOLDEN