

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
207	STD	10-43	45-08	232	232	177	177	.225	.225	.338	.338	.015	.011	HYD	HYD	106	108	149-202
402	STD	23-52	65-21	255	265	182	194	.232	.256	.348	.384	.023	.020	HYD	HYD	103	111	BLUE
427	STD	29-67	65-27	276	272	199	199	.258	.258	.387	.387	.028	.025	HYD	HYD	109	110	BLACK EFI
229	1	23-56	62-21	259	263	196	196	.242	.243	.363	.365	.028	.022	HYD	HYD	106	112	BLACK STD & TORQUE
403	1	21-60	63-19	260	262	201	202	.272	.272	.408	.408	.032	.028	HYD	HYD	108	111	
408	2	26-63	68-24	270	272	208	209	.280	.280	.420	.420	.040	.037	HYD	HYD	109	110	
228	2	27-66	66-25	270	270	208	208	.295	.295	.443	.443	.040	.037	HYD	HYD	109	111	
409	3	30-70	70-30	280	280	217	217	.285	.285	.428	.428	.052	.048	HYD	HYD	108	111	
218	4	35-75	75-35	290	290	225	225	.278	.278	.417	.417	.067	.060	HYD	HYD	108	108	202XUI (HX)
410	5	38-78	78-38	295	295	226	226	.305	.305	.458	.458	.060	.055	HYD	HYD	109	111	
197	5	32-70	70-30	280	280	230	230	.320	.320	.480	.480			HYD	HYD	108	111	
417	6	43-81	77-41	304	298	241	240	.333	.333	.500	.500	.086	.083	HYD	HYD	111	108	
219	6	40-80	80-40	300	300	241	241	.300	.300	.450	.450	.075	.070	HYD	HYD	107	111	202 BATHURST XUI (XJ)
656	1	16-55	67-15	252	257	195	202	.268	.260	.402	.390	.023	.020	HYD	HYD	110	112	GAS
217		30-66	60-27	275	267	200	200	.230	.230	.345	.345	.032	.028	HYD	HYD	106	108	186 XUI

CODE: HOLDEN 6 HYD
 PERFORMANCE - 46G
 STANDARD - 46S
 BILLET - EP35
 EXCHANGE - DEP H6

6 HYD

ROCKER RATIO 1.5

HOLDEN