

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
229	STD	23-56	62-21	259	263	196	196	.242	.243			.028	.022	HYD	HYD	106	112	
512	1	24-54	69-22	270	270	199	198	.250	.250			.017	.015	HYD	HYD	107	113	TURBO STD CAM
656	1	16-55	67-15	252	257	195	202	.268	.260			.023	.020	HYD	HYD	110	112	
521	2	27-67	72-29	274	282	202	207	.265	.265			.035	.032	HYD	HYD	110	110	
409	3	30-70	70-30	280	280	217	217	.285	.285			.052	.048	HYD	HYD	108	111	
737	3	30-68	69-28	277	277	214	214	.295	.295			.048	.042	HYD	HYD	109	109	

CODE: HOLDEN VLRB30
 PERFORMANCE - 46G
 - 46HFSC2V
 STANDARD - 46S
 BILLETT - EPS 503
 EXCHANGE - DEP VLRB30

NOTES: NON ADJUSTABLE TAPPETS
 HEAD OR CAM FOLLOWER CARRIERS CAN BE MACHINED
 TO PRE LOAD FOLLOWERS.
 CAM GRINDS BIGGER THAN STG 1 REQUIRES A BILLETT CAM.
 PROFILES ARE THE SAME AS PUSHROD HYD.

VLRB30

HOLDEN