

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
705	STD	32-74	82-38	286	299	196	198	.242	.245	.365	.368			.010	.012	108	110	
339	1	18-58	70-30	249	280	184	194	.230	.248	.347	.372	.028	.052	.010	.012	109	110	
666	1	25-64	70-30	269	282	201	202	.263	.264	.398	.397	.038	.032	.010	.012			
645	2	25-66	74-32	275	286	198	220	.245	.253	.372	.382	.055	.078	.008	.010	110	110	

CODE: MAZDA FE/F8
 PERFORMANCE - 44GOHC
 STANDARD - 44SOHC
 BILLETT FE - EP154
 BILLETT F8 - EP146
 EXCHANGE - DEP FE/F8

NOTES: FE DIST GEAR AT REAR OF CAM - FRONT WHEEL DRIVE
 F8 DIST GEAR IS BETWEEN FRONT TWO JOURNALS
 - REAR WHEEL DRIVE

ROCKER RATIO 1.55

FE/F8

MAZDA