

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
607	STD	15-58	60-18	253	258	196	198	.216	.218	.361	.363	.030	.016	.006	.008	112	112	
265	STD	8-50	52-13	238	245	180	180	.215	.210	.360	.349			.006	.008	112	109	
269	STD	17-58	56-17	255	253	199	200	.215	.215	.360	.358			.006	.008			
268	1	24-65	70-29	269	279	212	213	.215	.215	.360	.358			.006	.008			
542	2	33-70	86-46	282	313	222	225	.230	.230	.385	.383	.045	.028	.006	.008	107	108	
645	3	25-66	74-32	275	286	198	220	.245	.253	.409	.420	.055	.078	.008	.010	110	110	

CODE: MITSUBISHI 4G32 BELT
 PERFORMANCE - 44GOHC
 STANDARD - 44SOHC
 BILLETT - NIL
 EXCHANGE - DEP 4G32B

NOTES: 2 CAMS EARLY. LONG NOSE THEN PUMP LOBE
 LATE MODEL. SHORT NOSE/GEAR/PUMP LOBE

4G32 BELT

ROCKER RATIO 1.7

MITSUBISHI