

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
230	STD	14-52	48-12	246	240	190	190	.237	.235	.281	.279	.017	.015	.015	.015	108	107	STD 1100
582	STD	21-50	57-25	250	262	200	215	.264	.264	.318	.315			.012	.015	105	109	STD 1100s (1275)
233	1	29-56	60-27	266	268	216	216	.265	.265	.316	.316	.050	.045	.015	.015	107	107	STD 1275 COOPER S
509	2	26-57	62-24	263	266	221	223	.270	.270	.323	.323	.060	.055	.015	.015	105	111	POLICE PURSUIT
485	2	35-50	73-32	264	286	214	225	.262	.264	.316	.316	.062	.058	.012	.014	103	110	
212	3	35-72	73-34	287	287	230	230	.277	.277	.331	.331	.065	.060	.015	.015	108	110	
235	3	46-75	71-44	301	298	228	227	.260	.260	.310	.310	.070	.065	.015	.015	105	108	731 FACTORY
238	3	38-80	80-36	298	296	233	233	.312	.312	.375	.375	.068	.065	.015	.015	106	110	544 FACTORY
400	4	42-73	78-40	295	298	234	243	.311	.320	.377	.385	.091	.090	.012	.015	104	108	
667	4	30-67	64-30	277	274	231	230	.323	.323	.390	.392	.070	.065	.014	.012	106	107	
239	5	43-76	68-41	300	290	245	244	.325	.325	.391	.391	.112	.105	.015	.015	100	104	648 FACTORY
244	6	52-80	75-56	312	312	259	258	.347	.347	.419	.419	.115	.105	.015	.015	100	101	
240	6	48-70	72-46	298	298	260	260	.325	.325	.391	.391	.145	.130	.015	.015	100	103	

CODE: MORRIS A
 PERFORMANCE - 44G
 STANDARD - 44S
 BILLET - NIL
 EXCHANGE - NIL

NOTES: 3 TYPES OF OIL PUMP DRIVES
 PIN, STAR, SLOT.
 2 LOBE WIDTHS 3/8 x 1/2

MINI
1100-1275

ROCKER RATIO 1.25

MORRIS A