

# WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
643	STD	15-60	63-12	255	255	193	193	.221	.221			.017	.015	.008	.010	112	114	
605	1	21-61	63-19	243	243	204	204	.238	.238			.028	.025	.010	.014	110	112	TORQUE GRIND
233	2	29-56	60-27	266	268	216	216	.265	.265			.050	.045	.015	.015	107	107	
509	3	26-57	62-24	263	266	221	223	.270	.270			.060	.055	.015	.015	105	111	
212	4	35-72	73-34	287	287	230	230	.277	.277			.065	.060	.015	.015	108	110	
124	5	59-69	94-57	308	330	249	251	.273	.273			.095	.088	.020	.022	105	107	
642		20-64	78-20	264	278	207	209	.283	0.271			.030	0030	.012	.014	113	113	TURBO
127		31-65	66-35	276	281	214	215	.265	.262			.052	.047	.012	.014	106	108	
667		30-67	64-30	277	274	231	230	.323	.323			.070	.065	.014	.012	106	107	

**CODE: NISSAN A10-A14-A15**

PERFORMANCE - 44G  
 STANDARD - 44S  
 BILLETT - NIL  
 EXCHANGE - DEP A12

**NOTES:** SPRINGS VS58143 = 75LB ON SEAT .510 LIFT  
 MORRIS COOPERS SPRINGS FIT  
 A10/A14/A15 ALL HAVE DIFFERENT PUMP & GEAR  
 COMBINATIONS.

\*ASK POSITION OF GEAR/GEARS & PUMP LOBE POSITONS\*  
 DON'T EXCHANGE WITHOUT ASKING CUSTOMER

**A10-A14-A15**

**NISSAN**