

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
697	STD	6-36	43-4	222	227	179	182	.223	.234	.335	.351	.018	.015			105	108	
605	1	21-61	63-19	243	243	204	204	.238	.238	.347	.343	.028	.025	.010	.014	110	112	
233	2	29-56	60-27	266	268	216	216	.265	.265	.383	.025	.050	.045	.015	.015	107	107	
509	2/3	26-57	62-24	263	266	221	223	.270	.270	.390	.390	.060	.055	.015	.015	105	111	
212	3	35-72	73-34	287	287	230	230	.277	.277	.401	.401	.065	.060	.015	.015	108	110	
126	4	34-64	65-32	278	277	225	223	.240	.235	.342	.333	.064	.058	.018	.020	107	107	
124	5	59-69	94-57	308	330	249	251	.273	.273	.390	.388	.095	.088	.020	.022	105	107	
667	6	30-67	64-30	277	274	231	230	.323	.323	.471	.473	.070	.065	.014	.012	106	107	
207	STD	10-43	45-8	232	232	177	177	.225	.225	.338	.338	.015	.011	HYD	HYD	106	108	5K
423	1	16-47	60-16	243	256	181	195	.231	.253	.347	.380			HYD	HYD	106	113	5K
408	2	26-63	68-24	270	272	208	209	.280	.280	.420	.420	.040	.037	HYD	HYD	109	110	5K
127		31-65	66-35	276	281	214	215	.265	.262	.386	.379	.052	.047	.012	.014	106	108	
125		50-87	82-48	316	309	246	242	.267	.260	.381	.368	.085	.075	.020	.022	108	108	
485		35-50	73-32	264	286	214	225	.262	.264	.381	.382	.062	.058	.012	.014	103	110	

CODE: TOYOTA 3K-5K

PERFORMANCE - 44G
 STANDARD - 44S
 BILLETT - EP COROLLA
 EXCHANGE - DEP 3K

NOTES: 1. MANY DIFFERENT HEADS AVAILABLE
 2. CHECK SPRINGS FOR COIL BINDS

ROCKER RATIO 1.5

3K - 5K

TOYOTA