

WAGGOTT CAMS

No.	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
			Advertised		@.050"		Cam		Valve		@T.D.C.						
	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
110	37-73	71-35	290	286	226	224	.235	.225	.401	.381	.062	.061	.006	.008	108	108	
107	32-68	68-30	280	278	228	227	.295	.295	.492	.492	.065	.058	.018	.018	108	108	
212	35-12	73-34	287	287	230	230	.277	.277	.464	.464	.065	.060	.015	.015	108	110	
732	30-70	74-28	280	280	243	244	.297	.297	.493	.493	.077	.072	.020	.020	110	114	GTHO Phase 3
466	32-64	68-30	276	278	249	250	.338	.339	.565	.564	.105	.101	.020	.022	107	109	
755	35-67	76-36	282	291	247	257	.330	.342	.551	.572	.098	.098	.020	.020	103	113	
467	34-63	73-32	277	285	249	258	.360	.365	.597	.605	.113	.092	.026	.026	106	110	
104	47-78	80-48	305	308	251	254	.325	.330	.542	.549	.104	.104	.020	.022	105	108	
250	40-84	86-44	304	310	255	259	.325	.330	.542	.549	.109	.109	.020	.022	107	109	

CODE: FORD CLEVELAND SOLID
 PERFORMANCE - 48G
 STANDARD - 48S
 BILLET - EP 21
 SOLID FOLLOWERS -AT2000

CLEVELAND - SOLID

FORD

ROCKER RATIO 1.73