

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
229		23-56	62-21	259	263	196	196	.242	.243	.387	.389	.028	.022	HYD	HYD	106	112	STD RED
656	1	16-55	67-15	252	257	195	202	.268	.260	.429	.416	.023	.020	HYD	HYD	110	112	TORQUE & ST 1 GAS
521	1.5	27-67	72-29	274	282	202	207	.265	.265	.424	.424	.035	.032	HYD	HYD	110	110	ST2 GAS
404	1.5	21-60	63-19	258	258	206	206	.283	.282	.467	.465	.037	.027	HYD	HYD	108	112	
408	2	26-63	68-24	270	270	209	209	.291	.291	.480	.480	.043	.033	HYD	HYD	107	111	
737	3	30-68	69-28	275	275	213	213	.291	.291	.480	.480	.048	.042	HYD	HYD	107	111	
409	3	30-70	70-30	280	280	217	217	.291	.291	.480	.480	.052	.048	HYD	HYD	107	111	
545	4	34-70	74-32	285	285	222	222	.291	.291	.480	.480	.055	.050	HYD	HYD	107	111	
386	4	34-70	74-32	285	286	222	226	.311	.311	.513	.513	.063	.056	HYD	HYD	107	111	
387		37-68	75-35	286	290	224	228	.311	.311	.513	.513	.066	.061	HYD	HYD	107	111	
388		39-73	79-37	292	296	230	234	.311	.311	.513	.513	.076	.069	HYD	HYD	107	111	
389		40-74	80-38	294	298	232	236	.311	.311	.513	.513	.079	.072	HYD	HYD	107	111	
390		40-74	80-38	294	298	232	236	.331	.331	.546	.546	.080	.073	HYD	HYD	107	111	
391		41-75	81-39	296	300	234	238	.331	.331	.546	.546	.082	.075	HYD	HYD	107	111	
392		44-78	84-42	302	306	240	244	.331	.331	.546	.546	.092	.085	HYD	HYD	107	111	
393		45-79	85-43	304	308	242	246	.331	.331	.546	.546	.095	.088	HYD	HYD	107	111	
395		49-83	89-47	312	316	250	254	.331	.331	.546	.546	.108	.100	HYD	HYD	107	111	
396		50-84	90-48	314	319	252	256	.331	.331	.546	.546	.111	.103	HYD	HYD	107	111	
394		41-75	80-40	292	296	238	242	.351	.351	.579	.579	.092	.085	HYD	HYD	107	111	

CODE: HOLDEN V8 HYD
 PERFORMANCE - 48G
 STANDARD - 48S
 BILLET - EP5

NOTES: EFI MOTOR ON DIFFERENT SHEET
 SUIT RED, BLUE & BLACK

V8 HYD

ROCKER RATIO 1.65

HOLDEN