

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
777				252	256	225	229	.310	.310	.499	.499			.012	.012	108	112	
400				261	270	234	243	.310	.310	.499	.499			.012	.012	108	112	
667				257	261	230	234	.335	.335	.540	.540			.012	.012	107	111	
735				268	274	240	246	.335	.335	.540	.540			.012	.012	107	111	
601				270	276	242	248	.335	.335	.540	.540			.012	.012	107	111	
654				272	278	244	250	.335	.335	.540	.540			.012	.012	107	111	
240				274	279	246	252	.335	.335	.540	.540			.012	.012	107	111	
755				276	281	248	254	.335	.335	.540	.540			.012	.012	107	111	
164				278	283	250	256	.335	.335	.540	.540			.012	.012	107	111	
250				279	285	252	258	.335	.335	.540	.540			.012	.012	107	111	
993				287	291	260	264	.335	.335	.540	.540			.012	.012	107	111	
###				268	276	234	242	.340	.340	.549	.549			.012	.012	107	111	
123				278	284	252	258	.350	.350	.565	.565			.012	.012	107	111	
784				289	296	262	268	.350	.350	.565	.565			.012	.012	107	111	
###				290	295	264	269	.390	.390	.632	.632			.012	.012	106	106	

CODE: HOLDEN V8 SOLIDS
 PERFORMANCE - 48G
 STANDARD - 48S
 BILLETT - EP5

ROCKER RATIO 1.65

V8 SOLIDS

HOLDEN